



## DECLARATION OF PERFORMANCE

NO: DoP0985F6717-13956-W

### 1.Product Type:

Unique identification code of the product –type:

TRC EPDM

### 2.Type:

Batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

EPDM Waterproofing Membrane (White on Black)  
1,50mm,1.52mm,2.00mm & 2.30mm

### 3.Intended use:

Or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Elastomeric roof waterproofing sheet made of Ethylen-Propylen-Dien-Terpolymer (EPDM) according to EN 13956, used as roof waterproofing membrane in fully adhered and mechanically attached roofing systems as defined by EN 13956

### 4.Name,registered Trade name

Or registered trade mark and contact address of the manufacture as required under Article 22(5):

TECHNO RUBBER COMPANY LTD  
SECOND INDUSTRIAL CITY, PO BOX: 3508, DAMMAM,  
KINGDOM OF SAUDI ARABIA

### 5.Contact Address:

Where applicable, am and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Refer point 4

### 6.AVCP:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

### 7.Notified body:

In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Notified Factory production control certification body No.1922 & No.0836 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of Factory Production Control and issued the certificate of conformity of the factory production control, 1922-CPR-0985 & UK 0836-CPR-23/F6717

### 8. Notified Body:

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant (see 7)

SECOND INDUSTRIAL CITY,P.O BOX :3508 ,DAMMAM 34326,KINGDOM OF SAUDI ARABIA



شركة المطاط الفني  
TECHNO RUBBER COMPANY

### 9. Declared performance: (White on Black)

Essential Characteristics	Unit	Test Standard	Declared Value
Length	Mtr	EN 1848-2	-0%,+5%
Width	Mtr	EN 1848-2	-0.5%,+1%
Effective Thickness	mm	EN 1849-2	-5%,+10%
Mass per unit area	kg/m <sup>2</sup>	EN 1849-2	-5%,+10%
Joint peel resistance	N/50mm	EN 12316-2	≥25
Joint shear resistance	N/50mm	EN 12317-2	≥150
Tensile strength	N/mm <sup>2</sup>	EN 12311-2	≥8.0
Elongation at break	%	EN 12311-2	≥300
Resistance to impact (Hard support)	mm	EN 12691 (A)	≥200
Resistance to static load(Hard support)	Kg	EN 12730 (B)	≥10.0
Tear resistance	N	EN 12310-2	≥ 25.0
Dimensional stability	%	EN 1107-2	±0.5
Reaction to Fire	-	EN 13501-1	Class E
External Fire Performance	-	EN 13501-5	B roof (t1)
Foldability at Low Temp	°C	EN 495-5	≤-45
UV Exposure	-	EN 1297	Pass
Water permeability (100kPa for 24hrs)	-	EN 1928	Pass
Resistance to Ozone	-	EN 1844	Pass
Solar reflectance	-	ASTM C1549	0.80
Thermal Emittance	-	ASTM C1371	0.90
Solar Reflectance Index (SRI)	-	ASTM E 1980	101

### 10. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:



Rajasekaran.S  
QC & Coding,  
Techno Rubber Company Ltd,  
Dammam, KSA.  
Issue Date: 02-08-2025  
Rev Date: 24-11-2025

SECOND INDUSTRIAL CITY, P.O BOX :3508 ,DAMMAM 34326, KINGDOM OF SAUDI ARABIA

TEL: (+966)13-8123333 , FAX: (+966)13-8123322

Email: [info@technorubber.com.sa](mailto:info@technorubber.com.sa)  
Website: [www.technorubber.com.sa](http://www.technorubber.com.sa)

**Dedal**  
Attestation &  
Certification

ISO 9001  
BUREAU VERITAS  
Certification

