



DECLARATION OF PERFORMANCE

NO: DoP1871-13864_2020

1. Product Type:

Unique identification code of the product –type:

TRC EPDM FF
(Apperance: Fabric Finish)

2. Type:

Batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Effective Thickness
(0.75mm,1.00mm,1.20mm & 1,52mm)
(lot no.see packaging) – Type A

3. Intended use:

Or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Non reinforced, black, Rubber membrane made of Ethylen-Propylen-Dien-Terpolymer (EPDM) according to EN 13984:2013, used as a Flexible sheets for waterproofing - Plastic and rubber vapour control layers - Definitions and characteristics(Type-A)

4. Name,registered Trade name

Or registered trade mark and contact address of the manufacture as required under Article 22(5):

TECHNO RUBBER COMPANY LTD
SECOND INDUSTRIAL CITY, POBOX: 3508,
DAMMAM,
KINGDOM OF SAUDI ARABIA

5. Contact Address:

Where applicable, am and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Refer point 4

6. AVCP:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 3 – Annex ZA.4

7. Notified body:

In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Tests carried out at 1871

SECOND INDUSTRIAL CITY,P.O BOX :63658 ,DAMMAM,KINGDOM OF SAUDI ARABIA

[TEL:\(+966\)13-8123333](tel:+96613-8123333) ,[FAX: \(+966\)13-8123322](tel:+96613-8123322)

[Email: info@technorubber.com.sa](mailto:info@technorubber.com.sa)

[Website: www.technorubber.com.sa](http://www.technorubber.com.sa)

ISO 9001
BUREAU VERITAS
Certification



8. Notified Body:

Not relevant (see 7)

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

9. Declared performance:

Essential Characteristics	Unit	Test Standard	Performance Value	Harmonized Technical Specification
Visible defects	-	EN 1850-2	Pass	EN 13984:2013
Length	Mtr	EN 1848-2	-0,+5%	
Width	Mtr	EN 1848-2	-0.5 , +1%	
Thickness	mm	EN 1849-2	-5 ,+10%	
Straightness	mm	EN 1848-2	≤50	
Mass per unit area	Kg/m ²	EN 1849-2	-5 ,+10%	
Water tightness	-	EN 1928	Pass	
Resistance to Impact	mm	EN 12691	≥150	
Resistance to Tearing(Nail shank)	N	EN 12310-1	≥20	
Joint strength	N/50mm	EN 12317-2	≥200	
Tensile strength	N/mm ²	EN 12311-2	≥6.0	
Elongation	%	EN 12311-2	≥300	
Reaction to Fire	-	EN 13501-1	Class E	
Water vapour transmission (Moisture resistance factor)	-	EN 1931	73,600	
Resistance to alkali	--	EN 1847	Pass	
Durability of water vapour resistance against ageing (Not more than ± 50% change)	--	EN 1296	Pass	

10. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:




Rajasekaran.S
Techno Rubber Company Ltd,
Dammam, KSA.
Issue Date: 01.04.2021
Rev Date: 28.11.2025

SECOND INDUSTRIAL CITY, P.O BOX: 63658, DAMMAM, KINGDOM OF SAUDI ARABIA

TEL:(+966)13-8123333 ,FAX: (+966)13-8123322

Email: info@technorubber.com.sa

Website: www.technorubber.com.sa

ISO 9001
BUREAU VERITAS
Certification

